DM™603 S2

Floor-standing loudspeaker system

Product Summary

- The DM603 S2 is the entry level floor standing speaker in the 600 Series2. The speaker
 comes into its own as a front speaker in larger Home Cinema installations and, as with
 any model in the range, it is a superb monitor for 2-channel audio.
- The 2¹/₂-way system uses a second bass-only driver to supplement the output of the upper bass/midrange driver in the lowest octaves. This arrangement improves system power handling and reduces demands on the bass/midrange driver, which in turn improves midrange clarity.

Technical highlights



Nautilus™ Tweeter: B&W's Nautilus Tweeter technology ensures that the sound remains focused and time-sensitive and that the stereo-image is presented with unparalleled three dimensional accuracy.



Kevlar®: B&W developed and patented the method of using Kevlar® for loudspeaker cones to reduce unwanted standing waves. DuPont originally created Kevlar® for use in bulletproof vests.

WHAT HI-FI?

Awarded the Home Cinema Speakers -Best Buy Speaker Package along with the 601S2 and CC6S2 What Hi-Fi Awards 1999



Description Nominal impedance 8 (min 4.3) 21/2-way vented-box system Drive units Power handling 25W - 150W into 8 ohm on unclipped 1 x 25mm metal dome high-frequency 1 x 180mm woven Kevlar® cone Dimensions Height: 850mm Width: 236mm bass/midrange Depth: 306mm 1 x 180mm paper/Kevlar® cone bass Frequency response $48Hz - 20kHz \pm 3dB$ on reference Finishes Cabinet: Cherry or Black Ash Vinyl. Grilles: Black cloth Sensitivity 90dB spl (2.83V, 1m)

